

Excess effective Debye temperature of binary liquid mixtures from sound velocity measurements at 298.15K

V Vyas*, P Jain and T Nautiyal

Department of Chemistry, University of Allahabad,
Allahabad 211 002, India

E-mail vimala_vyas@rediffmail.com

Received 8 May 2002, accepted 24 June 2003

Abstract The excess effective Debye temperature (θ_D^E) has been evaluated for six binary mixtures, namely: n-heptane + toluene, n-heptane + n-hexane, toluene + n-hexane, cyclohexane + n-heptane, cyclohexane + n-hexane, n-decane + n-hexane over entire range of mole fractions at 298.15 K using the experimental data of ultrasonic velocity and density. The results thus obtained have been interpreted in the light of intermolecular interactions and modifications of the internal structure of the mixtures.

Keywords Debye temperature, binary liquid mixtures, ultrasonic velocity.

PACS Nos. 82.60.Lf, 43.35.Bf

1. Introduction

As compared to solids, the study of atomic motions in liquid state is more complex. The study of water by Hughes *et al* [1] shows that the atomic motion of water resembles the solid rather than the gaseous phase. Rigidity and fluidity both exist in liquid over a short time, other properties are also different. The structure of liquids can be denoted by the term quasicrystalline in the same way that they display a certain degree of local order of the same type as that of the corresponding crystal. The study of dynamics of atomic motions in liquids plays a very important role in understanding the solid-like behaviour of liquids. A number of theoretical and experimental evidences [2-5], now are available which support the quasicrystalline model for liquids. Assuming atomic motion in liquids to be similar to a solid, attempts were made [4] to calculate the Debye temperature. Assuming the quasicrystalline model for the liquids, the study [6] of Debye temperature has been extended to other liquids and interesting results were obtained. Although some study has been done on θ_D in liquids, yet it is difficult to have a clear understanding of the physical significance of θ_D in liquids. It can only be suggested that θ_D has more or less the same

meaning as in solids. It should be mentioned here that study on the variations of effective Debye temperature of aqueous solutions of non-electrolytes with the mole fractions are found to be highly useful in delineating the solute-solvent interactions. Kor and coworkers [7, 8] calculated the effective Debye temperatures of water, methanol, ethanol, carbon tetrachloride and toluene as a function of temperature and pressure. Recently, [9, 10] effective Debye temperature of few binary mixtures of non-electrolytes has been computed. Literature survey indicates that this type of study on binary mixture is very scanty. The aim of this paper is to evaluate the effective Debye temperature θ_D and excess effective Debye temperature θ_D^E of six binary liquid mixtures, which have been evaluated from experimentally measured values of sound velocity and density at 298.15 K. Intermolecular interactions and modifications of structure of the mixtures have been interpreted on the basis of excess effective Debye temperature.

2. Experimental

All the organic liquids were used of Analar grade and obtained from BDH Chemicals Ltd, England. These chemicals are further purified. Densities were determined with the help of standard bicapillary pycnometer technique used by other workers [11].

* Corresponding Author

This pycnometer is self-filling in type and offers accuracy up to 1 to 4 parts in 10^4 . The pycnometer was immersed in the thermostatic bath maintained at 298.15 K. In the present work, sound velocity measurements were made by a crystal-controlled ultrasonic interferometer supplied by M/s Mittal Enterprises at 2MHz frequency with an accuracy of 0.3%. The excess molar volumes were computed from measured sound velocity and density data. Experimentally determined sound velocity and density data have been compared with literature values [12].

3. Theoretical

The expression used in evaluating the effective Debye temperature is given by

$$\theta_D = \frac{K}{N} \left(\frac{9N}{4\pi V} \right) \left[\frac{1}{u_l^3} + \frac{2}{u_t^3} \right]^{1/3} \quad (1)$$

where

h is the Planck constant,

K is the Boltzmann constant,

N is the Avogadro's number,

u_l and u_t are longitudinal and transverse wave velocities

and V is the Molar volume of the specimen.

The velocities u_l and u_t of the longitudinal and transverse waves respectively can be written in terms of the isothermal compressibility β_T and the density as follows:

$$\frac{1}{u_l^3} + \frac{2}{u_t^3} = (\rho \cdot \beta_{T\infty})^{1/2} \left[\frac{2(1+\sigma)}{3(1-2\sigma)} + \left(\frac{1+\sigma}{3(1-\sigma)} \right) \right] \quad (2)$$

$$u_l = \left[\frac{1+\sigma}{3(1-\sigma)} \right]^{-1/2} [\rho \cdot \beta_T]^{-1/2} \quad (3)$$

$$u_t = \left[\frac{2(1+\sigma)}{3(1-2\sigma)} \right]^{-1/2} [\rho \cdot \beta_T]^{-1/2} \quad (4)$$

Poisson's ratio σ , for liquids exhibiting the quasi-crystalline properties, can be computed as follows:

$$\sigma = \frac{(3A-2)}{(6A+2)} \quad (5)$$

The value of A is obtained in terms of principal specific heat ratio (γ) and is given by

$$A = \left[\frac{4}{3} \cdot \frac{1}{\gamma} \right] \quad (6)$$

where $\gamma = C_p / C_v = \beta_T / \beta_s$,

Thus, the effective Debye temperature θ_D can be obtained using equations (1) to (6). This procedure has been applied previously for the calculation of θ_D for cryogenic liquids and some binary liquid mixtures [13] as a function of temperature at various mole fractions.

In the present work, isothermal compressibility β_T has been calculated with the help of Anjani [14] relation

$$\beta_T = \left| \frac{1.71 \times 10^{-3}}{u^2 \cdot T^{1/2} \cdot \rho^{1/2}} \right| \quad (7)$$

The excess effective Debye temperatures have been evaluated by using the following expression :

$$\theta_D^E = \theta_{D(\text{exp})} - \theta_{D(\text{id})} \quad (8)$$

where

$$\theta_{D(\text{id})} = \frac{9N}{4\pi V_{\text{id}}} \left[\frac{1}{u_{l,\text{id}}^3} + \frac{2}{u_{t,\text{id}}^3} \right]^{1/3} \quad (9)$$

$$u_l(\text{id}) = \left[\frac{(1+\sigma_{\text{id}})}{3(1-\sigma_{\text{id}})} \right]^{-1/2} [\rho_{\text{id}} \cdot \beta_{T,\text{id}}]^{-1/2} \quad (10)$$

$$u_t(\text{id}) = \left[\frac{2(1+\sigma_{\text{id}})}{3(1-2\sigma_{\text{id}})} \right]^{-1/2} [\rho_{\text{id}} \cdot \beta_{T,\text{id}}]^{-1/2} \quad (11)$$

where the symbols have their usual meanings.

4. Results and discussion

Since liquid mixtures form a part of study of liquid state, an attempt has been made here to assess the values of effective Debye temperature θ_D and excess effective Debye temperature θ_D^E for six binary mixtures; n-heptane + toluene, n-heptane + n-hexane, toluene + n-hexane, cyclohexane + n-heptane, cyclohexane + n-hexane, n-decane + n-hexane by using the experimental data of ultrasonic velocity and density measured at 298.15K. Table 1 lists the value of θ_D and other related parameters for the pure components at 298.18K.

Longitudinal and transverse wave velocities u_l and u_t have been evaluated using eqs. (1) to (6). The u_l and u_t data have been used to calculate the effective Debye temperature using eq. (1). The effective Debye temperature and other related parameters evaluated for the said mixtures are given in Tables 2 to 7. $u_l(\text{id})$ and $u_t(\text{id})$ have been evaluated by employing eqs. (10) and (11). The $u_l(\text{id})$ and $u_t(\text{id})$ obtained are used in the evaluation of $\theta_{D(\text{id})}$. The excess effective Debye temperature θ_D^E values for all the mixtures evaluated using eq. (8), are also recorded in Tables 2 to 7.

Table 1. Density (ρ), ultrasonic velocity (u), isentropic compressibility (β_s) and effective Debye temperature (θ_D) of pure component liquids at 298.15 K

Pure component liquids	ρ gcc ⁻¹	u ms ⁻¹	β_s 10 ¹² cm ² dyne ⁻¹	θ_D K
Toluene	0.8626	1304.6	68.15	71.99
Cyclohexane	0.7736	1253.0	82.47	69.18
n-hexane	0.6548	1078.2	131.96	55.46
n-heptane	0.6793	1130.6	115.13	55.94
n-decane	0.7260	1225.0	91.79	56.53

Table 2. Density (ρ), ultrasonic velocity (u), specific heat ratio (γ), Poisson's ratio (σ), Effective Debye temperature (θ_D) and excess effective Debye temperature (θ_D^E) at different mole fractions (X_1) for the binary liquid mixture n-heptane + toluene.

X_1	ρ gcc ⁻¹	u ms ⁻¹	γ	σ	θ_D (K)	θ_D^E (K)
0.2979	0.8693	1247.0	1.4239	0.1061	58.0	-1.1
0.3162	0.8667	1243.0	1.4254	0.1059	57.7	-1.2
0.3325	0.8637	1240.5	1.4271	0.1056	57.5	-1.3
0.3519	0.8601	1237.2	1.4291	0.1052	57.3	-1.5
0.3707	0.8564	1233.7	1.4211	0.1047	57.0	-1.6
0.3902	0.8532	1230.0	1.4329	0.1044	56.7	-1.8
0.4029	0.8500	1228.0	1.4347	0.1040	56.5	-1.9
0.4282	0.8468	1224.0	1.4366	0.1036	56.2	-2.0
0.4484	0.8433	1220.0	1.4948	0.0919	55.9	-2.2
0.4684	0.8394	1216.0	1.4407	0.1028	55.6	-2.4
0.4874	0.8363	1213.8	1.4425	0.1024	55.4	-2.5
0.5023	0.8225	1211.0	1.4506	0.1008	54.9	-2.8
0.5227	0.8188	1206.5	1.4527	0.1004	54.6	-3.0
0.5442	0.8153	1203.7	1.4527	0.0999	54.4	-3.2
0.5646	0.8122	1199.0	1.4567	0.0995	54.1	-3.3

Examination of the data presented in Tables 2 and 3 shows that the value of θ_D^E is positive for the mixture n-heptane + n-hexane and negative for the mixture, n-heptane + toluene, throughout the concentration range. Examination of the data presented in Tables 4 and 5 shows that θ_D^E is positive for the mixtures toluene + n-hexane and cyclohexane n-heptane. Perusal of Tables 6 and 7 shows that θ_D^E is positive for the mixtures cyclohexane + n-hexane, throughout the concentration range except binary mixture n-decane + n-hexane which has some negative values at lower concentration of n-decane.

The positive value of excess effective Debye temperature θ_D^E may be attributed to the enhancement of short-range order in the mixtures and the negative θ_D^E may be attributed to the decrease of the short range order in the mixture compared to the order prevailing in pure liquids, thereby indicating that the

Table 3. Density (ρ), ultrasonic velocity (u), specific heat ratio (γ), Poisson's ratio (σ) Effective Debye temperature (θ_D) and excess effective Debye temperature (θ_D^E) at different mole fractions (X_1) for the binary liquid mixture, n-heptane + hexane.

X_1	ρ gcc ⁻¹	u ms ⁻¹	γ	σ	θ_D (K)	θ_D^E (K)
0.3388	0.6614	1091.1	2.0502	0.00829	52.7	5.9
0.3598	0.6628	1092.2	2.0384	0.00635	52.6	5.9
0.3782	0.6606	1093.9	2.0402	0.00666	52.6	5.9
0.4001	0.6639	1094.4	2.0184	0.00306	52.4	5.7
0.4193	0.6636	1095.1	2.0108	0.00180	52.3	5.7
0.4394	0.6646	1096.5	1.9994	0.00099	52.1	5.5
0.4604	0.6656	1097.0	1.9878	0.00202	52.1	5.5
0.4782	0.6663	1098.5	1.9776	0.00374	52.0	5.5
0.4986	0.6672	1199.6	1.9659	0.00571	52.5	5.9
0.5191	0.6681	1101.8	1.9531	0.00786	51.9	5.4
0.5395	0.6693	1102.8	1.9414	0.00986	51.8	5.3
0.5594	0.6729	1104.0	1.8958	0.01761	51.4	5.0
0.5795	0.6716	1104.9	1.8921	0.01831	51.3	4.9
0.6025	0.6730	1105.6	1.8788	0.02061	51.1	4.8
0.6135	0.6736	1106.0	1.8695	0.02224	51.0	4.7

Table 4. Density (ρ), ultrasonic velocity (u), specific heat ratio (γ), Poisson's ratio (σ) Effective Debye temperature (θ_D) and excess effective Debye temperature (θ_D^E) at different mole fractions (X_1) for the binary liquid mixture, toluene + n-hexane

X_1	ρ gcc ⁻¹	u ms ⁻¹	γ	σ	θ_D (K)	θ_D^E (K)
0.4074	0.7936	1149.7	1.4679	0.0973	52.93	4.2
0.4299	0.7984	1153.3	1.4649	0.0979	53.18	4.4
0.4486	0.8018	1159.5	1.4629	0.0983	53.53	4.7
0.4919	0.8111	1167.0	1.4573	0.0994	53.72	4.7
0.5114	0.8157	1172.0	1.4546	0.0999	54.00	4.9
0.5290	0.8188	1176.0	1.4522	0.1050	54.32	5.2
0.5491	0.8236	1181.0	1.4481	0.1012	54.52	5.3
0.5584	0.8278	1183.0	1.4474	0.1014	54.88	5.6
0.5880	0.8323	1188.0	1.4448	0.1029	55.05	5.7
0.6275	0.8400	1199.1	1.4403	0.1019	55.32	5.8
0.6453	0.8512	1203.6	1.4340	0.1042	55.62	6.1
0.6637	0.8527	1208.2	1.4332	0.1043	55.93	6.3
0.6829	0.8537	1213.1	1.4326	0.1044	56.48	6.8

mixtures n-heptane + n-hexane, toluene + n-hexane are less compressible than their pure components and the mixture n-heptane + toluene is more compressible than the individual components.

The results of calculation presented here exhibit the possibility of existence of effective Debye temperature in binary liquid mixtures. Magnitudes of θ_D obtained for all the liquid

Table 5. Density (ρ), ultrasonic velocity (u), specific heat ratio (γ), Poisson's ratio (σ) Effective Debye temperature (θ_D) and excess effective Debye temperature (θ_D^E) at different mole fractions (X_1) for the binary liquid mixture, cyclohexane + n-heptane

	ρ g/cc ⁻¹	u ms ⁻¹			θ_D (K)	θ_D^E (K)
0.2227	0.7184	1156.0	1.5175	0.0874	49.92	1.1
0.2689	0.7214	1162.1	1.5154	0.1878	50.39	1.3
0.3158	0.7236	1167.8	1.5138	0.0881	50.82	1.6
0.3588	0.7191	1171.8	1.5169	0.0876	51.01	1.6
0.4016	0.7243	1177.2	1.5133	0.0880	51.50	1.9
0.4433	0.7207	1182.0	1.5090	0.0891	51.99	2.2
0.4861	0.7334	1187.7	1.5071	0.0895	52.44	2.4
0.5270	0.7361	1191.9	1.5052	0.0899	52.82	2.6
0.5642	0.7384	1196.0	1.5036	0.0901	53.17	2.8
0.6019	0.7412	1201.2	1.5018	0.0905	53.60	3.0
0.6414	0.7438	1205.8	1.4999	0.0909	53.99	3.2
0.6795	0.7463	1210.6	1.4983	0.0912	54.40	3.4
0.7164	0.7482	1215.9	1.4971	0.0914	54.81	3.7
0.7521	0.7518	1220.0	1.4946	0.0920	55.20	3.9
0.7877	0.7547	1224.0	1.4928	0.0923	55.58	4.1

Table 6. Density (ρ), ultrasonic velocity (u), specific heat ratio (γ), Poisson's ratio (σ), Effective Debye temperature (θ_D) and excess effective Debye temperature (θ_D^E) at different mole fractions (X_1) for the binary liquid mixture, cyclohexane + n-hexane

	ρ g/cc ⁻¹	u ms ⁻¹			θ_D (K)	θ_D^E (K)
0.2189	0.6821	1110.0	1.5439	0.0822	48.98	1.0
0.2541	0.6860	1118.8	1.541	0.0828	49.48	1.4
0.2981	0.6914	1134.9	1.537	0.0836	50.35	2.2
0.3150	0.6932	1135.0	1.5375	0.0839	50.40	2.2
0.3647	0.6990	1142.3	1.5314	0.0847	50.90	2.5
0.3897	0.7022	1149.8	1.5290	0.0852	51.33	2.9
0.4258	0.7065	1155.4	1.5259	0.0858	51.70	3.2
0.4777	0.7129	1163.2	1.5214	0.0867	52.24	3.6
0.5029	0.7157	1170.0	1.5194	0.0871	52.63	3.9
0.5675	0.7232	1180.3	1.5141	0.0881	53.31	4.4
0.5799	0.7250	1182.7	1.5128	0.0884	53.47	4.5
0.6012	0.7275	1188.9	1.5111	0.0887	53.83	4.8
0.6695	0.7356	1200.0	1.5055	0.0898	54.57	5.4
0.7187	0.7415	1210.6	1.5046	0.0905	55.23	5.9
0.7888	0.7499	1221.8	1.4959	0.0917	56.00	6.5

mixtures at all compositions are reasonable and encouraging. A careful perusal of the Tables indicate that effective Debye temperature θ_D depends on composition of the binary liquid mixtures and the different trends followed are primarily due to the different types of molecular interactions in the different

Table 7. Density (ρ), ultrasonic velocity (u), specific heat ratio (γ), Poisson's ratio (σ) Effective Debye temperature (θ_D) and excess effective Debye temperature (θ_D^E) at different mole fractions (X_1) for the binary liquid mixture, n-decane + n-hexane.

	ρ g/cc ⁻¹	u ms ⁻¹			θ_D (K)	θ_D^E (K)
0.0187	0.6663	1075.5	1.5561	0.0799	46.79	-0.5
0.0588	0.6697	1080.1	1.5535	0.0804	46.68	0.3
0.1008	0.6730	1087.9	1.5508	0.0809	46.69	0.0
0.1436	0.6774	1094.6	1.5475	0.0816	46.69	0.3
0.1896	0.6777	1100.0	1.5472	0.0816	46.50	0.4
0.2348	0.6850	1108.4	1.5417	0.0827	46.63	0.9
0.2886	0.6883	1118.8	1.538	0.0832	46.68	1.3
0.3350	0.6917	1127.5	1.5368	0.0836	46.73	1.6
0.3872	0.6943	1135.4	1.5348	0.0840	46.69	1.9
0.4449	0.6987	1142.8	1.5316	0.0847	46.64	2.2
0.5009	0.7012	1152.3	1.5297	0.0850	47.18	3.1
0.5627	0.7071	1161.9	1.5255	0.0859	46.71	3.0
0.6248	0.7099	1173.9	1.5235	0.0863	46.80	3.4
0.6944	0.7114	1184.1	1.5224	0.0865	46.75	3.7
0.7655	0.7144	1195.6	1.5204	0.0869	46.78	4.1
0.8421	0.7191	1205.4	1.5690	0.0875	46.74	4.5
0.9191	0.7232	1218.6	1.5142	0.0881	46.85	4.9

systems. Thus for the present study, we conclude that liquid mixtures like other pure liquids and liquid metals, retain a solid-like characters and can be treated on the basis of the quasicrystalline model showing some reasonable magnitude for the effective Debye temperature.

References

- [1] D Hughes, H Palensky, W Kley and E Tubelo *Phys. Rev.* **119** 872 (1960)
- [2] E A Moelwyn-Hughes *Physical Chemistry* (London: Pergamon) (1965)
- [3] D Tabor *Gases, Liquids & Solids* (Penguin) (1969)
- [4] P A Egelstaff *Thermal Neutron Scattering* (New York: Academic) (1965)
- [5] J D Pandey *Acustica* **35** 87 (1976)
- [6] J D Pandey *Indian J. Chem.* **14A** 607 (1976)
- [7] S K Kot and N D Tripathi *J. Phys. Soc. Jpn* **36** 552 (1974)
- [8] S K Kor, R Prasad and A Agarwal *Acustica* **29** 239 (1973)
- [9] J A Bhavani, T Ramanjappa, E Rajagopal and N Manohar Murthy *Indian J. Pure Appl. Phys.* **33** 633 (1995)
- [10] P K Torongey, T Ramanjappa and N Manohar Murthy *Indian J. Pure Appl. Phys.* **36** 26 (1998)
- [11] S Magazir, P Magliardo, A M Musolino and M T Scioetino *J. Phys. Chem.* **101** 2348 (1997)
- [12] *CRC Hand Book of Chemistry & Physics* (Boca Raton, Florida: C.R.C. Press) 60th ed. (1980)
- [13] J D Pandey *Acoustics Lett* **3** 90 (1979)
- [14] J D Pandey, G P Dubey, N Tripathi and A, K Singh *J. Int. Acad. Phys. Sci.* **1** 117 (1997)